

## 28W 1500MM LINCOLN T8 CCT SWITCHABLE LED POULTRY TUBE WITH UVA, CABLE AND PLUG AND PLAY CONNECTORS

3% UVA CHIPS PROMOTE NATURAL BEHAVIOUR

COLOUR TEMPERATURE SWITCHABLE

UP TO 90% ENERGY SAVINGS COMPARED TO TRADITIONAL LIGHTING

0-100% DIMMABLE TO SIMULATE SUNRISE AND SUNSET







## **FEATURES AND BENEFITS**

- Unlike humans, birds can see the UV spectrum
- This helps them identify each other via UV reflectors in their plumage
- Promotes natural behaviour
- Reduces stress and undesirable behaviour like pecking
- Colour temperature switchable 5000K/Blue to calm birds; 2700K/Red to aid sexual development and egg production
- For full product specification see datasheet for GL7007 GL7012

## **PRODUCT INFORMATION**

Input: 180-240VAC 50/60Hz Output Current: 520mA Product Size (mm): 1500L x 28D Luminous Flux: 3500 lm Lumen Per Watt: 125 lm Inrush Current: 9A Flicker Free: (Hz): 0 Dimmable: 0.2-100% Surge Protection Voltage: 2000V Cable (mm): 2 X 1.00<sup>2</sup>

## **PRODUCT VARIATIONS**

 GL7284 With rotatable ends and double ended cable and male and female connectors

 5000K/Blue Switchable with UVA Chips (Diffused)

 GL7285 With rotatable ends and single ended cable and male connector

 5000K/Blue Switchable with UVA Chips (Diffused)

 GL7288 With rotatable ends and double ended cable and male and female connectors

 2700K/Red Switchable with UVA Chips (Diffused)

 GL7289 With rotatable ends and single ended cable and male connector

 2700K/Red Switchable with UVA Chips (Diffused)

 GL7289 With rotatable ends and single ended cable and male connector

 2700K/Red Switchable with UVA Chips (Diffused)

 GL7289 With rotatable ends and single ended cable and male connector

 2700K/Red Switchable with UVA Chips (Diffused)

 CRI
 PF

 67
 IM

 180
 Imode Tool (180%)

 CRI
 PF

 0.85
 Imode Tool (180%)